



COMMERCIAL HEATING SOLUTIONS



WALL HEAT

CONVECTOR/RADIANT

UNIT/DUCT HEATERS

PORTABLE

CEILING



SSAR™ ARCHITECTURAL

Sleek modern design
Digital touch screen LCD thermostat
BMS compatible
Energy efficiency with proportional heating
120V, 208V, 240V, 277V
900W to 4800W



INFRARED



IR technology heats the object and not the air = energy savings
Clean, energy-efficient alternative to propane/gas = no fumes
Perfect for indoor/outdoor applications with multiple finishes and mounting options
120V-600V units available from 1.5kW-13.5kW



MUH

3kW - 50kW / 208V, 240V, 277V, 480V
Horizontal and downflow capability
Long directed heat throw
Smooth quiet operation



MEDH (DRAGON HEATER)

Portable electric high capacity blower heater for applications where open flame is not allowed
Perfect for outdoor work areas or construction sites
208V, 240V, and 480V in 10kW to 30kW sizes



CDF Surface enclosure or recessed
3 adjustable airflow patterns
Built in fan delay
Automatic thermal cutout
208V, 240V, 277V up to 5kW




SSHO SMART SERIES®

High output digital programmable touch screen
BMS Compatible
Instant heat where and when you need it
208V, 240V, 277V
1800W to 4000W



PANEL HEAT

Easy to install and flexible application
Gentle heat with no noise or maintenance needed
Available in 120V, 208V, 240V, 277V, 347V
Invisible heat— silk screening to match any panel



CABINET

Use in hallways, entryways, classrooms & hospitals—limitless applications
Floor, ceiling or wall mounted
Fully customizable for your unique application or stock units available



AWH

BMS Compatible with relay
Fan delay preventing cold air discharge
Manual reset overheat protection
Totally enclosed motor
120V, 208V, 240V, 277V
1500W to 4800W



DBA/SHA

Selection, beauty, and performance—customizable for any decor and heating need
Floor, wall, or pedestal mount with bottom or front inlet
Built-in wireway and multiple entry points for ease of system installation
Aluminum, 120V-600V, 200W to 7500W+



DBSL

Slim, compact design customizable for any decor and heating need
Floor, wall, or pedestal mount with bottom or front inlet
Built-in wireway and multiple entry points for ease of system installation
Aluminum, 120V-600V, 200W to 2500W+



MSPH PLENUM HEATER

Concealed space zero clearance plenum rated
High limit thermal cutout—automatic reset.
Built-in disconnect switch
208V, 240V, 277V, 480V / 3-15kW



HARSH ENVIRONMENT

QWD WASHDOWN

Corrosion resistant 304 stainless steel
Totally enclosed motor
Nema 4x junction box protects controls against water
Automatic reset limit
120V, 208V, 240V, 277V, 480V, 600V
2-39kW



QCH Built-in power on/off switch.
Thermal cutout to shut off heater in case of overheating
Fan delay energizes fan motor only after elements
120V, 208V, 240V, 277V
1000W to 2000W



CWH ARCHITECTURAL

Fast heat response, compact design
Contemporary bar stock for optimized airflow
Fan delay preventing cold air discharge
120V, 208V, 240V, 277V
500W to 2000W



SLQDB

Compact, customizable design with 6" install height perfect for under the window, heat loss prevention
Built-in wireway and multiple entry points for ease of system installation
Aluminum, 120V-600V, 200W to 1880W+



CPH, DPH

Perfect for under the window, heat loss prevention
Floor, wall, or pedestal mount with bottom or front inlet
Built-in wireway and multiple entry points for ease of system installation
Steel, 120V-600V, 250W to 7500W



DUCT HEATERS

Open coil and finned tube available
Slip in or flanged installations
Made to order for complete customization



MWUH

Ceiling mount bracket for horizontal/vertical air throw
Built-in thermostat (45-90F)
Automatic fan delay
Dual voltage (208V/240V), up to 7500W



FOR MORE INFORMATION ON COMMERCIAL HEATING SOLUTIONS CLICK HERE TO CONTACT 3E