

# 320A Meter Main Pedestal Combination

U6317 Series



U6317-O-2/200-K3L

## Features & Benefits

- UL listed
- 320A continuous rating
- 4 terminal or 5 terminal
- Ringless design
- Two 200A Milbank UQFPH 22K AIC main breakers
- Heavy duty lever bypass jaw-clamping meter socket
- Anti-rotation lugs are available on line side
- Sockets with -5T9 have factory installed 5th terminal
- Side wireway trough to separate utility power from end user
- Pedestal has incoming line side chaseway and outgoing chaseway for load side wires
- Type 3R enclosure constructed with G90 galvanized steel
- Light gray polyester powder coat finish
- Direct burial pedestal suitable for free standing or structure mounted installation
- Separate line and load wireways with removable, lockable and sealable covers
- Extension kit: K6355

Catalog Number	Service	Hub	Term	Connectors CU/AL		Bypass	Dimensions			Concentric K.O.'s
				Line	Load		H"	W"	D"	
U6317-O-100-200-K3L	UG	Blank	4	#4-600 kcmil or (2)250 kcmil	#3-#1	Lever	80	15	4 <sup>3</sup> / <sub>32</sub>	2.5"
U6317-O-2/150-K3L	UG	Blank	4	#4-600 kcmil or (2)250 kcmil	1/0-300 kcmil	Lever	80	15	4 <sup>3</sup> / <sub>32</sub>	2.5"
U6317-O-2/200-K3L	UG	Blank	4	#4-600 kcmil or (2)250 kcmil	1/0-300 kcmil	Lever	80	15	4 <sup>3</sup> / <sub>32</sub>	2.5"
U6317-X-2/200-5T9	UG	Blank	5	#4-600 kcmil or (2)250 kcmil	1/0-300 kcmil	Lever	80	15	4 <sup>3</sup> / <sub>32</sub>	2.5"

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

